



NOTE:
300004MB004GX002L

- 1.SELECTIVE PLATING
G1-05u" GOLD OVER NICKEL.
G2-GOLD FLASH OVER 30 U"MIN,NICKEL.
G3-10u" GOLD OVER NICKEL.
G4-15u" GOLD OVER NICKEL.
G5-30u" GOLD OVER NICKEL.
G6-50u" GOLD OVER NICKEL.

NOTES:
1.THIS DIMENSION SHOULD KEEP 4.0~6.0mm
DURING BATTERY INSTALLATION(AFTER LIFE TEST)
2.LIFE CYCLE OVER 5000 TIMES(TESTING STORK=2.5MM)
3.WORKING HEIGHT 1.5 CONTACT FORCE 70~130 GRAMS
4. MAXIMUN STROKE 1.50 mm
5. CONTACTRESISTANCE<40m
6. CURRENT: 1A
7. RATED VOLTAGE : DC 20V
8.**SYMBOLS INDICATE KEY DIMENSIONS

EC1BE-110505-05	E	11'/05/05	E1:變更包裝結構	謝昌林	陳新杰	General	X±0.25	X'±3'	DESIGN	謝昌林	11'/04/11	
EC1BS-100924-08	D	10'/09/24	D1:新增尺寸1.5;D2:新增尺寸5.6	方林坤	陳新杰	X±0.20	X'±2'	CHECK	蔣武向	11'/04/11		
EC1BU-091221-07	C	09'/12/21	C1:變更叉片結構	唐靜	謝日倉	XX±0.15	XX'±1'	CHECK				
EC1B-060812-08	B	06'/08/12	B1:更換圖號;B2:重標CPKR尺寸	覃佐忠	葉銘良	XXX±0.08		APPRO.	陳新杰	11'/04/11		
ECN(DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED			APPRO.	陳新杰	11'/04/11	

3	FORK	PHO.BRONZE	TIN PLATED
2	TERMINAL	PHO.BRONZE	GOLD PLATED
1	HOUSING	BLACK	UL 94V-0
NO.ID DESCRIPTION		MATERIAL	COLOR
REMARK			

實盈 SUYIN CONNECTOR

CUSTOMER TITLE: 3.00mm PTHC BATTERY CONN--GRADE

PART NO. 300004MB004GX002L

PRODUCT SPEC. 300004MB

FILE NAME: 300004MB004GX002L-C

SCALE: 2:1 UNIT:mm A4 SHEET: 1 of 2